



Husqvarna FS 400

Our robust FS 400 LV is a convenient all-round petrol push floor saw. The adjustable handle ensures an ergonomic working position. Perfect weight distribution gives excellent stability while sawing. Ideal for small road repair jobs in concrete or asphalt, up to 162 mm cutting depth.



EASY TO OPERATE

Productive and robust with excellent weight distribution and stability.



ADJUSTABLE HANDLES

Provides a closer and more comfortable position to the cutting side for easier alignment and straighter cuts. Handle can also be folded for transport.



EASY TO TRANSPORT

Compact saw that is easy to lift.



LARGE INTEGRATED WATER TANK

Quick connection for water hose to the blade guard. No tools required for dis-assembly.

Features Husqvarna FS 400

- Engine and blade shaft mounting system increases comfort and gives excellent cutting performance.
- The handwheel can be folded when moving the saw to avoid breakage.
- Adjustable for all blade diameters.

TECHNICAL DATA	
Motor manufacturer	Honda
Motor spec	GX390
Max output (As rated by the engine manufacturer)	8,7 kW / 11,7 hp
Engine/motor RPM	pos1:3600 rpm
Cylinders	1
Number of strokes	4-stroke engine
Cylinder displacement	389 cm ³
Cylinder bore	88 mm
Cylinder stroke	64 mm
Fuel tank volume	6,1 lit
Air filter type	Cyclone dry dual
Starter	Recoil
Engine cooling	Air
Belt	Poly V
Oil capacity, l	1,1 lit
Diamond blade, max	450 mm
Max cutting depth	162 mm
Spindle diameter	25,4 mm
Blade depth control	Handwheel
Blade rotation	Downcut
Blade shaft drive	Poly-V belt
Blade flange	114,3 mm
Blade shaft RPM	3000 rpm
Arbor size	25,4 mm
Axle front	20 mm
Handle bars	Fixed, low vibration
Primary wheel size	Outside diameter: 125 Wheel width: 35 Inner bore: 20 mm
Secondary wheel size	Outside diameter: 200 Wheel width: 35 Inner bore: 20 mm
Wheel description primary	Aluminium with bearings & seals
Wheel description secondary	Aluminium with bearings & seals
Blade guard attachment	Bolted
Blade guard capacity	457,2 mm
Blade guard type	Fixed
Water tank volume	30 lit
Water safety device	Integrated water tank
Weight	99 kg
Weight incl. packaging	125 kg
Product size, LxWxH	1150x590x940 mm
Sound power level, guaranteed (LWA)	106 dB(A)
Sound pressure	96 dB(A)
Hand arm vibration (Aeq)	3,5 m/s ²

