



Chicago Pneumatic



CPG 120

People. Passion. Performance.



Over 100 years of experience

Since 1901 the Chicago Pneumatic name has represented high-performance tools and equipment designed for an extensive range of applications. Today, Chicago Pneumatic has a global reach, with local customer centers around the world. Chicago Pneumatic tools, air compressors and generators are tailored to the needs of the industrial, vehicle service, and construction markets. Every day we develop and manufacture new products that are meant to meet your demands not only today, but tomorrow as well.

To learn more about our extensive range of tools, hydraulic attachments, industrial and portable compressors, generators, accessories and workshop equipment, please visit www.cp.com.

Since 1901 the Chicago Pneumatic name has represented high performance tools and equipment designed for an extensive range of applications. Today, Chicago Pneumatic has a global reach, with local customer centers around the world. Chicago Pneumatic tools, air compressors and generators are tailored to the needs of the industrial, vehicle service, and construction markets. Every day we develop and manufacture new products that are meant to meet your demands not only today, but tomorrow as well.

To learn more about our extensive range of tools, hydraulic attachments, industrial and portable compressors, accessories and workshop equipment, please visit www.cp.com.

Standard Features

- Reliable John Deere engine and Stamford alternator
- 27.1 hour run time at 75% load with integrated 170 gallon in-frame fuel tank
- Environmentally friendly 110% fluid containment frame
- Solid-state digital controller with easy-to-read analog gauges
- Very quiet 67 dB(A)
- Electronic governor for increased voltage stability (0.25%)
- Remote start connections

Options

- Skid-mounted
- Battery charger
- Coolant heater
- Spare tire
- Tool box
- Rear stabilizer jacks
- External fuel connections

Technical Data

| Model | CPG 120 |
|---|------------------|
| Rated Standby Power | 106 kW / 133 kVA |
| Rated Prime Power | 95 Kw / 120 kVA |
| Voltage Selections - 1Ø | 120/240 |
| Voltage Selections - 3Ø | 208/240/480 |
| Amperage Capacity @ 120 volts 1Ø | 2 x 333 |
| Amperage Capacity @ 240 volts 1Ø | 333 |
| Amperage Capacity @ 208 volts 3Ø | 333 |
| Amperage Capacity @ 240 volts 3Ø | 288 |
| Amperage Capacity @ 480 volts 3Ø | 144 |
| Sound Pressure Level @ 23 feet @ 75% load | 67 dB(A) |
| Fuel Tank Capacity | 170 gal. |
| Fuel Consumption At 75% Load | 5.9 gal/hr |
| Fuel Autonomy At 75% Load | 27.1 hr |

| Engine | John Deere |
|---------------------|-------------------|
| Model number | 4045HF285 |
| Rated Speed | 1800 rpm |
| Emission Compliance | EPA Tier III |
| Rated Output | 158 HP @ 1800 rpm |
| Coolant | Water / Glycol |
| Cylinders | 4 |
| Displacement | 4.5 L |
| Engine Control | Electronic |

| Alternator | Stamford |
|---|------------|
| Model | UCI 274 CI |
| Degree Of Protection / Insulation Class | IP23 / H |

| Convenience Receptacles | |
|------------------------------------|---|
| 20 amp - 125 volt GFCI duplex | 2 |
| 50 amp - 125 / 250 volt twist lock | 2 |

| Dimensions (LxWxH) & Weight | |
|---------------------------------|------------------|
| Dimensions, mounted on skid | 112 x 44 x 67 in |
| Weight, wet, mounted on skid | 5,360 lbs |
| Dimensions, mounted on trailer | 176 x 78 x 80 in |
| Weight, wet, mounted on Trailer | 6,610 lbs |

The information contained herein is general in nature and is not intended for specific construction, installation or application purposes.